

Portable & User-Friendly

YC-1800

OPHTHALMIC YAG LASER SYSTEM



OPHTHALMIC YAG LASER SYSTEM YC-1800

Portable & User-Friendly Design

■ Improved Operability

The **"Smart Switch"** (patent pending) located on the joystick provides high operability, allowing doctors to change parameters (Energy up, Energy down and Ready/Standby *) while holding the joystick.

Permits faster and easier operation, and eliminates need to look away from oculars to make parameter adjustments.

* Factory setting.

The user has three choices from among energy up, energy down, ready/standby, aiming up, aiming down, burst and reset.



Unique Joystick **"Smart Switch"**

■ One-Touch Lock

The YC-1800 can smoothly slide back and forth and around, and the unit can be easily fixed and released at anywhere you like with the one-touch lock, offering high operability with improved safety.



■ Compact & Slim Design

The NIDEK YC-1800 is the smallest and lightest ophthalmic photodisruptor available and can be easily transported. Compact and slim design also allows greater flexibility in locating your arm rest.

■ Versatile Combo Lasers

The YC-1800 can be easily connected to NIDEK's Green Laser Photocoagulator (GYC-1000), allowing treatment of a wider range of patients and indications.

Space requirements are minimized, and the combination adapter (optional) includes the split mirror illumination tower.



The YC-GYC
changeover lever



Reliability and Safety

■ Reliable Laser Output

The YC-1800 employs the new technology to control the pulse number under the CPU **"D-Pulse"** (patent pending), providing higher stability against environmental conditions and change over time.

■ Fast Operation

The 3Hz firing rate is the fastest available, which can be very practical when encountering a moving eye or other patient difficulties. The YC-1800 can treat a wide variety of diseases, and its speed and efficiency allows comfortable operation.

■ Great Number of Energy Settings

The YC-1800 offers 0.3-10mJ, continuously adjustable in increments of 0.1mJ, allowing the most precise tissue effect.

■ Super Adjustable Nd:YAG Offset

The YC-1800 has the exclusive ability to adjust the offset ± 500 microns (25 micron steps) to best meet your varied clinical needs. A different offset can be used for PMMA, silicone or acrylic lenses, and the offset can even be adjusted on the same IOL to compensate for a parallax effect in the periphery. This eliminates the need to manually defocus, permits a clear field of view, and minimizes lens pitting.

■ Safer Rotating Aiming Beam

The dual 635nm aiming beam offers superior visual sensitivity, which in turn enhances the speed and ease of operation. The 635nm beam is also safer to human eyes since it achieves the same crisp and sharp intensity of 650nm or 670nm beam with half the power output. The YC-1800 has the ability to rotate the dual aiming beams 360° permitting work anywhere in the periphery without clipping the iris.



360 degree-manual rotation of the aiming beam for precise operation.



YC-1800 Specifications

Treatment Laser	
Type	Nd:YAG
Wavelength	1064nm
Mode Structure	Fundamental
Pulse Duration	4 nsec
Mode of Operation	Q-switched
Pulse Repetition Rate	3Hz (single) / 1.5Hz (burst)
Output Energy	0.3-10.0mJ/pulse (Continuously variable)
Burst Mode	2 or 3 pulse/trigger
Spot Size	8µm
Cone Angle	16°
Focal Shift	0-500µm (Continuously variable, toward both anterior chamber and posterior chamber)
Aiming Laser	
Type	Diode laser
Wavelength	635nm
Output Power	OFF, 0.5-25µW
Cone Angle	16°
Aiming Method	Dual beam method
Rotation of Beam	360°
Slit Lamp	
Objective Lens	f=130mm
Eye Piece	12.5x
Magnification (field of view)	32x(6.2mm), 20x(10mm), 12.5x(16mm), 8x(25mm), 5x(40mm)
Power Supply	Single-phase, 100-240Vac, 50/60Hz, 100VA
Dimension / Weight	324 (W) x 407(D) x 528.5(H) mm / 16kg 12.8(W) x 16 (D) x 20.8 (H) * / 35.3lbs.
Standard Accessories	Head belt, Arm rest, Key switch, Slit lamp bulb, Chin rest pads
Optional Accessories	Motorized optical table, Foot switch, Safety goggles

*Manufacturer
NIDEK Co., LTD.
34-14, Maehama, Hiroishi, Gamagori, Aichi 443-0038, Japan

Caution: U.S. Federal Law restricts this device to sale, distribution and use by or on the order of a physician or other licensed eye care practitioner.



CE
0123

*Specifications and design are subject to change without notice for improvement.



Printed on environment-friendly recycled paper.

©NIDEK 2006 Printed in Japan YC-1800 NOEGM®



Eye & Health Care
NIDEK CO., LTD.

HEAD OFFICE
34-14 Maehama, Hiroishi
Gamagori, Aichi 443-0038, Japan
Telephone : 81-533-67-6611
Facsimile : 81-533-67-6610
URL : <http://www.nidek.co.jp>

TOKYO OFFICE
(International Div.)
3F Sumitomo Fudosan Hongo Bldg.,
3-22-5 Hongo, Bunkyo-ku, Tokyo,
113-0033 Japan
Telephone : 81-3-5844-2641
Facsimile : 81-3-5844-2642
URL : <http://www.nidek.com>

NIDEK INC.
47651 Westinghouse Drive
Fremont, CA 94539, U.S.A.
Telephone : 1-510-226-5700
: 1-800-223-9044 (US only)
Facsimile : 1-510-226-5750
URL : <http://www.usa.nidek.com>

NIDEK SOCIÉTÉ ANONYME
Europarc
13, rue Auguste Perret
94042 Créteil, France
Telephone : 33-1-49 80 97 97
Facsimile : 33-1-49 80 32 08
URL : <http://www.nidek.fr>

NIDEK TECHNOLOGIES SRL
Via dell'Artigianato, 6 / A
35020 Albignasego (Padova), Italy
Telephone : 39 049 8629200 / 8626399
Facsimile : 39 049 8626824
URL : <http://www.nidektechnologies.it>