

# T3A80B-4 0,75KW 230/400V B5

## Three-phase asynchronous motor in aluminium

Motor type T3A80B-4 0,75KW 230/400V B5  
 Brand BUSCK  
 Item number 93040812

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,75	50	3,3	1440
400	0,75	50	1,9	1440
460	0,86	60	1,9	1728

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	82,5
Insulation class	F	Efficiency, load 75%	82,5
Cooling	IC411 (TEFC)	Efficiency, load 50%	80,1
Max. ambient temp.	40°C	Power fact, load 100%	0,69
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	11
Torque, Nm	4,97	Sound pressure Lp dB(A)	58
Starting torque ratio	3,1	Bearing DE	6204-2Z
Pull up torque ratio	2,5	Bearing NDE	6204-2Z
Pull out torque ratio	3,1	Cable entries	1xM20, 1xM16
Starting current ratio	6,3		
Balance grade	Normal		
Inertia kgm <sup>2</sup>	0,00228456		
Winding protection	Thermocontacts		

