

# T3A112M-4 4KW 400/690V B35

## Three-phase asynchronous motor in aluminium

Motor type T3A112M-4 4KW 400/690V B35  
 Brand BUSCK  
 Item number 93041124

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	4	50	7,9	1450
690	4	50	4,54	1450
460	4,6	60	7,9	1740

Duty	S1	Efficiency class	IE3
Enclosure	IP55	Efficiency, load 100%	88,6
Insulation class	F	Efficiency, load 75%	88,8
Cooling	IC411 (TEFC)	Efficiency, load 50%	88,2
Max. ambient temp.	40°C	Power fact, load 100%	0,82
Min. ambient temp.	-20°C	Painting	Standard
Max. temp. rise	80 K	Color	RAL 9005
Max altitude, masl	1000	Weight kg	32
Torque, Nm	26,34	Sound pressure Lp dB(A)	65
Starting torque ratio	3,1	Bearing DE	6306-2Z
Pull up torque ratio	2,6	Bearing NDE	6206-2Z
Pull out torque ratio	3,7	Cable entries	2xM25, 1xM16
Starting current ratio	8,6		
Balance grade	Normal		
Inertia kgm <sup>2</sup>	0,0152916		
Winding protection	Thermocontacts		

