




**minipack® - torre**  
Packaging machines and systems

# SLEEVE WRAPPER MS 70 – 1E SEP

**AUTOMATIC SLEEVE WRAPPER WITH 1 TRACK LOADING BELT AT 90° AND  
ELECTRIC PUSHER**

with 700 mm sealing bar



## DESCRIPTION

---

minipack@torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



The new series of **Minipack-torre** sleeve wrappers stands out for the great versatility of the models offered combining efficiency, reliability and high performance.

The MS 70 - 1E SEP sleeve wrapper has a **1-track thermoplastic resin feed belt arranged at 90°**, driven by a variable speed motor and controlled by an inverter. It makes up to 12 packages per minute.

## TECHNICAL FEATURES

Power supply	V	220/400
Phase	ph	3
Electrical power	kW	24
Electric consumption	kWh	15
Air Pressure	bar	6
Air Consumption per cycle	nl	14
Hourly production	p/h (pph)	Up to 12 ppm
Sealing Bar	mm	700
MAX product height	mm	380
MAX reel dimensions	mm	Ø 350x680
Worktop height	mm	Standard 850+25
Machine dimensions	mm	3564x2068x h.1900
Tunnel infeed dimensions	mm	600x h.400
Tunnel chamber length	mm	1600
Machine weight	kg	1050

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.



## MAIN FEATURES

---

- Feed belt arranged at 90°
- Electric pusher with multi-row preassembly
- Sealing bar with a film cutting blade (no smoke during the sealing step)
- Height of the worktop: 850 +/-25mm
- Photoelectric cell that blocks the sealing bar if it encounters an obstacle in its path
- Passage opening under the sealing bar 230 mm
- Automatic wrapping system of the film reels with dragging rollers
- Heat-shrinking film reels with max diameter 350 mm - thickness between 35 and 100 microns
- Managed by PLC and TOUCH to change data and display the alarms for machine reset
- Real time monitoring of the alarms and direct editing of the machine settings with possibility of storing up to 10 formats
- The temperature of the sealing bar and the tunnel is controlled by the PLC
- Heat-shrinking tunnel insulated with rock wool and heated with resistors. Forced ventilation with air circulation
- Heat-shrinking tunnel Length 1600 mm with air circulation system
- Internal conveyor belt in the heat-shrinking Tunnel, driven by a gear motor with adjustable speed and featuring a thin steel mesh grate with side chains
- Switch to change the cycle from automatic to manual
- Installed power 24kW
- Average electricity consumption is reduced by about 40% during normal operation
- Air consumption 140 nl/min
- Pneumatic components that work with non-lubricated dry air
- Power supply: Option between 3phases 220V and 400V 3phases + N + T
- Machines compatible with Machinery Directive 2006/42/EC