



WRAPJET 30 INTEGRAL

AUTOMATIC SEAMLESS FILM SLEEVE WRAPPER WITH PLC AND MULTILINE DIVIDER (6 TRACKS) AND AUTOMATIC LOADING OF CARDBOARD TRAYS OR FLAPS, TRAY FORMER - ALSO FOR FILM ONLY

bundle packaging in film only, film + flap or film + tray



DESCRIPTION

The new series of **Minipack-torre** lines is characterised by the great versatility of the models on offer. In fact, they are able to package different types of goods, from cans of food preserves, to bottles, etc.

The WRAPJET 30 INTEGRAL automatic sleeve wrappers package any product **with or without the support of a cardboard flap or tray**.

With a WRAPJET 30 INTEGRAL sleeve wrapper it is possible to produce **up to 30 packages per minute** (depending on the product size), thanks to the packaging technique **without sealing bar**.

The WRAPJET line sleeve wrappers also allow you to make packages with customised films.

TECHNICAL FEATURES

Power supply	V	220/400
Phase	ph	3
Electrical power	kW	58
Electric consumption	kWh	55



Air Pressure	bar	6
Air Consumption per cycle	nl	5
Hourly production	p/h (pph)	Up to 30 ppm
MAX product height	mm	380
MAX reel dimensions	mm	Ø 400x700
Worktop height	mm	Standard 1000+25
Machine dimensions	mm	13500x1650x h.2150
Tunnel infeed dimensions	mm	700x h.400
Tunnel chamber length	mm	2900
Machine weight	kg	4900

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

MAIN FEATURES

- Seamless film machine without sealing bar
- Multi-row inline feeder
- Volumetric product sorting system
- Large capacity cardboard flap and tray store (up to 600 flaps) located under the machine
- Flap dimensions min. mm. 250x175 - max. mm. 550x450
- Tray dimensions min. mm. 200x150 - max. mm. 580x480 with edge height of mm. 35
- Edge height from mm. 35 to 70 mm.
- Option to package products with film only or film + flap or film + tray
- System for wrapping the film around the package by overlapping the film under the package, which self-glues while going through the tunnel
- Film feeding and cutting unit with rotating blade
- Manual sealer for film splice
- Ionising bars to remove the electrostatic charge which accumulates in the film reels
- Heat-shrinking film reels with max diameter 400 mm - thickness between 50 and 100 microns
- Height of the worktop: 1000 +/-25mm
- Managed by MICROPROCESSOR and TOUCH to change data and display the alarms for machine reset
- Wrapping bar control and cutting blade with BRUSHLESS motors
- Real time monitoring of the alarms and direct editing of the machine settings with possibility of storing up to 10 formats
- The tunnel temperature is controlled by the microprocessor
- Heat-shrinking tunnel insulated with rock wool and heated with resistors. Forced ventilation with air circulation
- Heat-shrinking tunnel Length 2900 mm with air circulation system
- Internal conveyor belt in the heat-shrinking Tunnel, driven by a gear motor with adjustable speed and

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



featuring a thin steel mesh grate with side chains

- o Switch to change the cycle from automatic to manual
- o Installed power 58kW
- o Average electricity consumption is reduced by about 40% during normal operation
- o Air consumption 80 nl/min
- o Pneumatic components that work with non-lubricated dry air
- o Power supply: Option between 3phases 220V and 400V 3phases + N + T
- o Machines compatible with Machinery Directive 2006/42/EC