



**Cryovac® IMPACT™** is a polyolefin shrink film with unsurpassed optics that promise the product will shine brightly on store shelves and its toughness ensure products will hold up under extreme conditions in production, packaging, shipping, retail stocking and consumer handling. Ideal for irregular shaped products & with sharp edges, it ensures high performance impact, tensile and trim seal strength.

Product range	Range	Plain SW			Plain CF			Pre-perf CF		
	Thickness (µ)	13	15	19	13	15	19	13	15	19
	Grade	16	19	24	16	19	24	16	19	24
	Perforation pattern	N/A	N/A	N/A	N/A	N/A	N/A	Conform Specification sheet		
	Printability	Yes/ Available at Sealed Air			Yes/ Available at Sealed Air			N/A	N/A	N/A
	Logo print	N/A			N/A			N/A		
	Minimum possible width (mm)	100	100	100	155	155	155	155	155	155
	Maximum possible width (mm)	1 600	1 600	1 600	905	955	1 055	905	955	1 055
	Increment	10	10	10	50	50	50	50	50	50
	Standard roll length (lm)	3 000	2 500	2 000	1 500	1 250	1 000	1 500	1 250	1 000
Core size	3	3	3	3	3	3	3	3	3	
Safety Stock Materials (SSM)	Widths	No safety stock available	<u>Epernon:</u> 400, 450, 500, 550, 600, 650, 700	No safety stock available	<u>St. Neots:</u> 605 - <u>Passirana:</u> 255, 355, 405, 455, 505, 555, 605 - <u>Epernon:</u> 255, 355, 405, 455, 505, 555	<u>St. Neots:</u> 305, 355, 405, 555, 605 - <u>Passirana:</u> 205, 255, 305, 355, 405, 455, 505, 555, 605, 655, 705, 755 - <u>Epernon:</u> 205, 255, 305, 355, 405, 455, 505, 555, 605, 655, 705, 755, 855	<u>St. Neots:</u> 355, 405, 455 - <u>Passirana:</u> 205, 255, 305, 355, 405, 455, 505, 555, 605, 655, 705, 755, 805 - <u>Epernon:</u> 205, 255, 305, 355, 405, 455, 505, 555, 605, 655, 705, 755, 805, 855, 905, 950, 1000	<u>Passirana:</u> 355, 405, 455, 505	<u>St. Neots:</u> 355, 405, 455 - <u>Passirana:</u> 305, 355, 405, 455, 505, 555, 605 - <u>Epernon:</u> 305, 355, 405, 455	<u>Passirana:</u> 355, 405, 455, 505, 555, 605 - <u>Epernon:</u> 355, 405, 455
Lead time	SSM (Standard material)	N/A	2 days + Transit	N/A	2 days + Transit time			2 days + Transit time		
	MTO (Make to order)	2 weeks + Transit time			3 weeks + Transit time			3 weeks + Transit time		
Minimum order qty	SSM (Standard material)	N/A	1 pallet	N/A	1 pallet			1 pallet		
	MTO (Make to order)	1 pallet			Up to 355: 1 pallet 355 to 555: 2 pallets 605-755: 3 pallets Above 805: 2 pallets			Up to 355: 1 pallet 355 to 555: 2 pallets 605-755: 3 pallets Above 805: 2 pallets		
Comments	SSM (Standard material)	N/A	Only 2 pallets can be taken in the given leadtime, for one customer.	N/A	Only 2 pallets can be taken in the given leadtime, for one customer.			Only 2 pallets can be taken in the given leadtime, for one customer.		
	MTO (Make to order)	Multiple length roll NOT available			Multiple length roll available and special price may apply due to pairing.			Multiple length roll available and special price may apply due to pairing.		
Sample rolls	Minimum order qty.	1 roll	1 roll	1 roll	1 roll (2 rolls for 155/255mm widths)			1 roll (2 rolls for 155/255mm widths)		
	Sample roll length (lm)	3 000	2 500	2 000	1 500	1 250	1 000	1 500	1 250	1 000

Pallet config.	SW				<b>STANDARD PALLET CONFIGURATION:</b> Small width (up to 200 - 250) 2 rolls packed per box, larger rolls boxed individually. For CF double length, above 855mm: 4 rolls per pack laid horizontally.  * No carton box (Export procedure)
	Roll width in mm	Nber of rolls/pall	Nber of rolls/layer	Nber of layers	
	100 - 120	72	24	3	
	130 - 170	54	18	3	
	180 - 250	36	12	3	
	260 - 350	27	9	3	
	360 - 550	18	6	3	
	560 - 770	12	4	3	
	780 - 1490	9	3	3	
	1500* ->	12	4	3	
CF					
Roll width in mm	Nber of rolls/pall	Nber of rolls/layer	Nber of layers		
155	54	18	3		
205 - 255	36	12	3		
305 - 355	27	9	3		
405 - 555	18	6	3		
605 - 755	12	4	3		
805 ->	9	3	3		

