

ANTHEM 29 2 (NX EAGLE)



SPECS

RAM	
STORLEK	S, M, L, XL
FÄRG	Black / Metallic Black / Metallic Green
RAM	ALUXX SL-Grade Aluminum
FRAMGAFFEL	Fox 32 Float SC Performance, 100mm travel, GRIP2 Damper, Boost 15x110mm KaBolt, tapered steerer
BAKDÄMPARE	Fox Float DPS Performance, trunnion mount
KOMPONENTER	
STYRE	Giant Contact SL XC flat, 780 x 31.8mm
STYRSTAM	Giant Contact
SADELSTOLPE	Giant Contact, 27.2mm
SADEL	Contact SL (forward)
PEDALER	N/A
DRIVPAKET	
VÄXELREGLAGE	SRAM NX Eagle, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	SRAM NX Eagle
BROMSAR	SRAM Level T [F] 180mm [R] 160mm, hydraulic disc
BROMS HANDTAG	SRAM Level T
KASSETTE	SRAM NX Eagle, 11x50
KEDJA	SRAM NX Eagle
VEVPARTI	TruVativ Descendent 6k Eagle Dub, Boost, 30
HJUL	
BOTTOM BRACKET	SRAM GXP Dub Press Fit
FÄLGAR	Giant XCT 29, tubeless ready, sleeve-joint rim, 25mm inner width
NAV	[F] Giant Tracker Performance Boost 15x110mm, sealed bearing [R] Giant Tracker Performance Boost 12x148, sealed bearing
EKRAR	Sapim
DÄCK	Maxxis Recon Race 29x2.25, foldable, TLR, 60tpi, EXO, tubeless

EGENSKAPER

- Ram: ALUXX SL-Grade Aluminum
- Framgaffel: Fox 32 Float SC Performance, 100mm travel, GRIP2 Damper, Boost 15x110mm KaBolt, tapered steerer
- Växelslag: SRAM NX Eagle, 1x12
- Vevparti: TruVativ Descendent 6k Eagle Dub, Boost, 30
- Färg: Black / Metallic Black / Metallic Green

Pris: 30 500 SEK

GEOMETRI

RAM	S	M	L	XL
Seat Tube Length (mm)	390	440	490	535
Seat Tube Angle	73,5°	73,5°	73,5°	73,5°
Top Tube Length (mm)	590	610	630	650
Head Tube Length (mm)	95	95	105	115
Head Tube Angle	69,0°	69,0°	69,0°	69,0°
Fork Rake (mm)	51	51	51	51
Trail (mm)	89	89	89	89
Wheelbase (mm)	1113	1133	1154	1175
Chain Stay Length (mm)	438	438	438	438
Bottom Bracket Drop (mm)	45	45	45	45
Stack (mm)	585	585	594	604
Reach (mm)	417	437	454	471
Stand Over Height (mm)	740	761	796	828
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	60	70	80	90
Crank Length (mm)	170	175	175	175
Wheel Size	29"	29"	29"	29"

Alla specifikationer kan ändras utan varsel.