



SPECS

RAM	
STORLEK	S, M, L, XL
FÄRG	Metallic Orange / Black
RAM	ALUXX SL-Grade Aluminum
FRAMGAFFEL	Fox 34 Float Performance Elite, 130mm travel, FIT4 Damper, Boost 15x110mm QR, tapered steerer
BAKDÄMPARE	Fox Float Performance Elite, trunnion mount
KOMPONENTER	
STYRE	Giant Contact SL, 780x35mm, 20mm rise
STYRSTAM	Giant Contact SL 35
SADELSTOLPE	Giant Contact Switch S dropper post with remote lever, 30,9mm
SADEL	Giant Contact SL (neutral)
PEDALER	N/A
DRIVPAKET	
VÄXELREGLAGE	SRAM GX Eagle, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	SRAM GX Eagle
BROMSAR	SRAM Guide R [F] 180mm [R] 180mm, hydraulic disc
BROMS HANDTAG	SRAM Guide R
KASSETTE	SRAM XG1275 Eagle, 10x50
KEDJA	SRAM GX Eagle
VEVPARTI	TruVativ Descendent 6k Eagle Dub, Boost, 30
HJUL	
BOTTOM BRACKET	SRAM GXP Dub Press Fit
FÄLGAR	Giant TRX 1 29 WheelSystem, hookless carbon, 30mm inner width
NAV	Giant TRX 1 29 WheelSystem
EKRAR	Giant TRX 1 29 WheelSystem
DÄCK	[F] Maxxis Minion DHF 29x2.3, 60 tpi, 3C, EXO, TR [R] Maxxis DHR II 29x2.3, 60 tpi, 3C, EXO, TR, tubeless

EGENSKAPER

- Ram: ALUXX SL-Grade Aluminum
- Framgaffel: Fox 34 Float Performance Elite, 130mm travel, FIT4 Damper, Boost 15x110mm QR, tapered steerer
- Växelslag: SRAM GX Eagle, 1x12
- Vevparti: TruVativ Descendent 6k Eagle Dub, Boost, 30
- Färg: Metallic Orange / Black

Pris: 44 000 SEK

GEOMETRI

RAM	S	M	L	XL
Seat Tube Length (mm)	380	431	482	507
Seat Tube Angle	74,5°	74,5°	74,5°	74,5°
Top Tube Length (mm)	592	612	632	652
Head Tube Length (mm)	95	110	110	120
Head Tube Angle	66,5°	66,5°	66,5°	66,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	117	117	117	117
Wheelbase (mm)	1154	1176	1196	1218
Chain Stay Length (mm)	435	435	435	435
Bottom Bracket Drop (mm)	35	35	35	35
Stack (mm)	599	613	613	622
Reach (mm)	426	442	462	480
Stand Over Height (mm)	708	740	761	785
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	50	60
Crank Length (mm)	170	175	175	175
Wheel Size	29"	29"	29"	29"

Alla specifikationer kan ändras utan varsel.