



SPECIFIKATIONER

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Core
SENSOR	Giant RideControl Dash
DISPLAY	Giant RideControl Dash
BATTERI	Giant EnergyPak 500, 36V 13.8Ah Rechargeable Lithium-Ion
RAM	
STORLEK	S, M, L, XL, XXL
FÄRG	Graphite
RAM	ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
FRAMGAFFEL	SR Suntour XCM ATB Coil 29" 100mm travel, Tapered 1½ - 1⅝" steerer
BAKDÄMPARE	N/A
KOMPONENTER	
STYRE	Giant Connect TR Riser 31.8x690-750mm
STYRSTAM	Giant Contact
SADELSTOLPE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADEL	Giant Sport
PEDALER	Aluminum Platform
DRIVPAKET	
VÄXELREGLAGE	Shimano M2010 9-Speed
FRAMVÄXEL	-
BAKVÄXEL	Shimano Alivio M3100, 9-Speed
BROMSAR	Tektro HD-M275, hydraulic disc, 160/180mm
BROMS HANDTAG	Tektro HD-M275
KASSETTE	Shimano CS-HG200, 11-36T
KEDJA	KMC e.9 Sport, e-bike optimized
VEVPARTI	Forged Alloy minimal Q-factor, 36T
VEVLAGER	N/A
HJUL	
FÄLGAR	Giant GX03V
NAV	Giant eTracker Sport, [F] 9mm QR [R] 135mm QR
EKRAR	Stainless steel
DÄCK	Maxxis Rekon Race 29 x 2.25, Wire Bead, Dual Compound 60TPI
EXTRA	Giant EnergyPak 4A Fast Charger
TILLBEHÖR	
BELYSNING	Herrmans H-BLACK MR4
PAKETHÅLLARE	Giant Rack-It MIK

EGENSKAPER

- Ram: ALUXX aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
- Framgaffel: SR Suntour XCM ATB Coil 29" 100mm travel, Tapered 1½ - 1⅝" steerer
- Växselreglage: Shimano M2010 9-Speed
- Vevparti: Forged Alloy minimal Q-factor, 36T
- Färg: Graphite

Pris: 33 000 SEK

GEOMETRI

RAM	S	M	L	XL	XXL
Seat Tube Length (mm)	405	468	505	535	560
Seat Tube Angle	73,0°	73,0°	73,0°	73,0°	73,0°
Top Tube Length (mm)	575	600	625	650	675
Head Tube Length (mm)	110	115	130	140	155
Head Tube Angle	68,0°	68,0°	68,0°	68,0°	68,0°
Fork Rake (mm)	46	46	46	46	46
Trail (mm)	100,7	100,7	100,7	100,7	100,7
Wheelbase (mm)	1150	1176	1202	1228	1254
Chain Stay Length (mm)	485	485	485	485	485
Vevlager (mm)	45	45	45	45	45
Stack (mm)	617	622	636	645	659
Reach (mm)	386	410	430	452	473
Stand Over Height (mm)	712	746	764	761	781
Bredd Styre (mm)	690	720	720	750	750
Längd Styrstam (mm)	50	60	60	70	80
Vevvarmlängd (mm)	165	165	170	170	170
Hjulstorlek	29"	29"	29"	29"	29"

Alla specifikationer kan ändras utan varsel.