

Dimension / Diameter / mm

S355JR (SS2172) Varmvalsat DIN 1013 Längd ca 6 meter	⊘	12 16 18 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 150 160 170 180 190 200
S355J2G3 M (SS2142IM) Varmvalsat DIN 1013 Längd ca 6 meter	⊘	40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 160 170 180 190
C45E (SS1672) Varmvalsat DIN 1013 Längd ca 6 meter	⊘	30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 150 160 170 180 190 200
S355JR (SS2172) Grovbearbetat, -0/+3mm Längd ca 4-6 meter	⊘	210 220 230 240 250 260 270 280 290 300 310 330 350 360 380 400 430 450 460 480 505
C45E (SS1672) Grovbearbetat, -0/+3mm Längd ca 4-6 meter	⊘	210 220 230 240 250 260 270 280 290 300 310 330 350 360 380 400 430 450 460 480 502 505 530 555 610
34CrNiMo6 (SS2541) Draget Tol. h9 Längd ca 6 meter	⊘	10 12 14 16 18
34CrNiMo6 (SS2541) Skalsvarvat Tol. h12 Längd ca 6 meter	⊘	16 18 20,8 22,8 25,8 28,8 30,8 32,8 36 39 41 43 46 51,2 56,2 61,2 66,2 71,4 76,4 81,4 86,4 91,4 96,4 102 107 112 117 122 127 132 138 143 153 163 173 178 184 194 203 214 224 235 242
25CrMo4 (SS2225) Skalsvarvat Tol. h12 Längd ca 6 meter	⊘	28,8 30,8 32,8 36 41 46 51,2 56,2 61,2 66,2 71,4 76,4 81,4 91,4 120 143
42CrMo4 (SS2244) Skalsvarvat Tol. h12 Längd ca 6 meter	⊘	22,8 25,8 32,8 36 41 46 51,2 56,2 61,6 66,2 71,4 76,4 81,4 91,4 102
34CrNiMo6 (SS2541) Smitt / Grovbearbetat, -0/+3 Längd ca 4-6 meter	⊘	225 265 275 285 293 306 313 330 363 383 400 413 420 435 450 460

		Dimension / Diameter / mm
42CrMo4 Draget h12	⊘	8 10 12 14 16 18
16NiCrS4 (SS2511) Draget Tol. h9 Längd ca 3-6 meter	⊘	12 14 16 18
16NiCrS4 (SS2511) Skalsvarvat Tol. h12 Längd ca 4-6 meter	⊘	20,8 22,8 25,8 28,8 30,8 32,8 36 39 41 43 46 51,2 56,2 61,2 66,2 71,2 76,2 81,4 86,4 91,4 96,4 102 107 112 117 122 127 132 143 153 163 173 184 194 200 210 220 230 250 260 275 290 306 330 356 380 406 430 455
C45E (SS1672) Ceax Tol. h8 Längd ca 3-6 meter	⊘	6 8 10 12 13 14 15 16 17 18 19 20 22 24 25 28 30 32 35 38 40 42 45 50 55 60 65 70 75 80 85 90 95 100 105 110 120 125
20MnV6 (SS2142) Ceax Tol. h8 Längd ca 6 meter	⊘	10 12 14 15 16 18 20 22 24 25 28 30 35 38 40 45 50 55 60 65 70 80 85 90 100 110
S355J2G3 (SS2172-06) Kalldraget Tol. h9 / h10 Längd ca 3-6 meter	⊘	4 5 6 8 10 12 13 14 15 16 17 18 19 20 22 24 25 38 30 32 35 38 40 42 45 50 55 60 80
11SMnPb28 (SS1914) Automatstål Tol. h9 Även 4-kt och 6-kt Längd ca 3 meter	⊘ □ ⬡	4 6 8 10 12 13 14 15 16 17 18 19 20 22 24 25 38 30 32 35 38 40 42 45 50 55 60 65 70 85 90 95 100 110 120 130 140
S235K (SS1312) Kalldraget Tol. h9 / h10	⊘	5 6 7 8 10 12 13 14 15 16 17 18 19 20
Triomax 1000 Slipad seghärdad stång 817M40, Likvärdigt SS2541-03 Tol. h8 Längd ca 3 meter	⊘	25 30 35 40 45 50 55 60 65 70 75 80 90 100
Valsad tryckkärilstång C 22.8 N + 13CRM04-5 (SS2216)	⊘	30 35 40 45 50 55 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200

Dimension / mm



S235JRG2 (SS1312)  
Varmvalsat platt  
Tol. DIN 1014  
Längd ca 5-6 meter  
Tol. över 150  
DIN 59200



S355JO (SS2132)  
Varmvalsat platt  
Tol. DIN 1014  
Längd ca 5-6 meter  
Tol. över 150  
DIN 59200

	3	4	5	6	8	10	12	15	20	25	30	35	40	50	60
12	■		■	■											
15		■	■		■	■									
20	■	■	■	■	■	■	■	■							
25	■	■	■	⊙	⊙	⊙	⊙	⊙	■						
30	■	■	⊙	⊙	⊙	⊙	⊙	⊙	⊙						
35	■	■	■	■		■	■	■	■						
40	■	■	⊙	⊙	⊙	⊙	⊙	⊙	⊙	⊙	■				
45			■		■	■	■	■	■	■					
50	■	■	⊙	⊙	⊙	⊙	⊙	⊙	⊙	⊙	⊙		⊙		
55				■											
60	■	■	■	⊙	⊙	⊙	⊙	⊙	⊙	⊙	⊙		⊙		
65						■									
70	■	■	■	⊙	⊙	⊙	⊙	⊙	⊙	⊙	⊙		⊙		
75		■	■	■	■	■	■	■						■	
80		■	■	⊙	⊙	⊙	⊙	⊙	⊙	⊙	⊙		⊙	⊙	
90			■	■	■	■	■	⊙	⊙	⊙	⊙				
100		■		⊙	⊙	⊙	⊙	⊙	⊙	⊙	⊙	⊙	⊙	⊙	
110			■			■	■	■			■				
120				■	■	⊙	⊙	⊙	⊙	⊙	⊙		⊙	⊙	⊙
130			■	■	■	⊙	⊙	⊙	⊙	⊙	⊙		⊙	⊙	
140					■	■	■	■	■	■					
150						⊙	⊙	⊙	⊙	⊙	⊙		⊙	⊙	
180							■	■	■		⊙				
200			■		■	■	■	■	■	■	■	⊙	⊙	■	
250						■		■	⊙		■				
300											⊙				
400											⊙				

S235JR C+C (SS1312-06)  
Kalldraget platt  
Tol. h11  
Längd ca 3-3,5 meter



S235JR C+C (SS1312-06)  
Kalldraget 4-kt  
Tol. h11  
Längd ca 3-3,5 meter



Dimension / mm

	2	3	4	5	6	8	10	12	15	20	25	30	35	40	50	60
10	◆	◆	◆	◆			+									
12	◆	◆	◆	◆	◆	◆	◆	+								
15	◆	◆	◆	◆	◆	◆			+							
18		◆	◆	◆	◆											
20	◆	◆	◆	◆	◆	◆	◆		◆	+						
25	◆	◆	◆	◆	◆	◆	◆	◆	◆		+					
30	◆	◆	◆	◆	◆	◆	◆	◆	◆	◆		+				
35		◆	◆	◆	◆	◆	◆	◆	◆	◆			+			
40		◆	◆	◆	◆	◆	◆	◆	◆	◆				+		
50		◆	◆	◆	◆	◆	◆		◆	◆					+	
60				◆	◆	◆	◆		◆	◆						+
70		◆			◆	◆	◆	◆	◆	◆	◆	◆				
75				◆												
80					◆	◆	◆	◆	◆	◆	◆					
100				◆	◆	◆	◆	◆	◆	◆	◆					
120						◆	◆		◆	◆						
130							◆									
150							◆		◆	◆	◆					
200							◆			◆						

Kilstål (212190)  
4-kt  
Längd ca 3-3,5 meter



Kilstål (212190)  
Platt  
Längd ca 3-3,5 meter



Dimension / mm

	4	5	6	7	8	9	10	11	12	14	15	16	18	20	22	25	28	30	32	35	36	40	45	
4	○																							
5		○																						
6			○																					
8				×	○																			
10				×	×	○																		
12				×	×		○																	
14					×				○															
15										○														
16						×					○													
18							×					○												
20								×					○											
22										×				○										
25										×					○									
28												×				○								
30																	○							
32													×					○						
35																			○					
36														×										
40															×							○		
45																×							○	
50																	×							
56																			×					
63																			×					
70																					×			