

**TRIO 2344/SS 2242**

Skalsvarvat utförande, Diameter i mm						
• 26,0	• 81,0	136,0	• 212,0	282,0	359,0	478,0
• 31,0	86,0	• 142,0	216,0	292,0	363,0	485,0
• 36,0	• 91,0	• 152,0	218,0	302,5	373,0	510,0
• 41,0	96,0	154,0	• 222,0	308,0	383,0	553,0
• 46,0	• 102,0	• 162,0	• 232,0	312,0	403,0	563,0
• 51,0	106,5	167,0	242,0	323,0	410,0	612,0
• 56,0	• 111,5	• 172,0	252,0	328,0	422,0	638,0
• 61,0	• 116,0	• 182,0	258,0	333,0	433,0	
• 66,0	• 122,0	• 192,0	262,0	343,0	448,0	
• 71,0	126,0	• 202,0	272,0	346,0	453,0	
• 76,0	• 132,0	206,0	276,0	353,0	460,0	

**TRIO 2363/SS 2260**

Skalsvarvat utförande, Diameter i mm						
10,0	• 30,8	• 60,8	• 96,0	• 151,5	• 212,0	• 323,0
• 12,7	• 35,8	• 66,0	• 101,5	• 161,5	• 230,0	• 353,0
• 18,0	• 40,8	• 71,0	• 111,5	• 170,0	• 240,0	
• 22,0	• 45,8	• 76,0	• 121,5	• 180,0	• 260,0	
• 25,8	• 50,8	• 81,0	• 131,5	• 190,0	• 280,0	
• 28,5	• 55,8	• 91,0	• 141,5	• 200,0	• 300,0	

**TRIO 2210/SS2140**

Slipat h8, Diameter i mm							
2,5	4,5	7	9,5	11,5	13,5	17	25
3	5	8	10	12	14	18	30
3,5	5,5	8,5	10,5	12,5	15	19	
4	6	9	11	13	16	20	

Dimensioner markerade med • = Lagerförs av TGS

### TRIO 2140/SS2140-02

Skalsvarvat utförande, Diameter i mm

31	36	41	51	61	71	81	91	102
----	----	----	----	----	----	----	----	-----

### TRIO 2379/SS 2310

Skalsvarvat utförande, dimensioner i mm

• 51,0	• 96,0	• 142,0	222,0	308,0	423,0	708,0
• 56,0	101,5	• 152,0	• 232,0	313,0	448,0	758,0
• 61,0	• 106,0	154,2	242,0	323,0	463,0	
• 66,0	• 112,0	• 162,0	• 252,0	333,0	483,0	
• 71,0	116,5	• 172,0	257,0	351,0	510,0	
76,0	• 121,0	• 182,0	262,5	363,0	532,0	
• 81,0	• 126,0	192,0	272,0	373,0	558,0	
83,7	128,8	• 202,0	282,0	383,0	563,0	
• 86,0	• 132,0	205,5	292,5	393,0	608,0	
• 91,0	• 136,5	• 212,0	302,5	410,0	658,0	

Dimensioner markerade med • = Lagerförs av TGS