

Transparent LED Displays

Unparalleled Transparency	Greater than 80% Transparency at highest resolution
Easy Setup	Plug and play. Super quick and easy for installation.
Light Weight	Only weighted 18kg/pcs (including hanging strings and power supplies). It weights half of most LED
High Brightness & Energy	With 6000nits (cd/m2) in brightness, the display is visible under direct sun light and can be used 24/7
Easy to Maintain	Long life expectancy (100,000 hrs) as replacement LED strips are swapped in easily without having to replace the entire panel.



Model:	UPLED-S	UPLED-M	UPLED-L
Pixel Pitch (mm)	3,33 x 6,66	3,13 x 6,66	2,5 x 5,71
Brightness (cd/m2)	6000	6000	6000
Transparency	68 %	68 %	64 %
Display Size (mm)	640 x 840	801 x 1127	960 x 1280
Cabinet Size (mm)	657 x 1014 x 51	817 x 1227 x 51	977 x 1440 x 51
Resolution (dot/m2)	24576	40960	86016
Module Resolution	192*128	256*160	384*224
Max. Power (w/m2)	600	720	970
Avg. Power (w/m2)	180	210	290
Ingress Protection	IP62	IP62	IP62
Input Power	AC100V-AC240V	AC100V-AC240V	AC100V-AC240V
Refresh Rate (Hz)	1000~1500	1000~1500	1000~1500
Weight (kg)	20	30	42
Working Temp.	-10 to +40 oC	-10 to +40 oC	-10 to +40 oC

