

LED-Modul

Unparalleled Transparency Greater than 80% Transparency at highest resolution

Easy Setup Plug and play. Super quick and easy for installation.

High Brightness & Energy Efficient With 6000nits (cd/m²) in brightness, the display is visible under direct sun light and can be used 24/7

Easy to Maintain Long life expectancy (100,000 hrs) as replacement LED strips are swapped in easily without having to replace the entire panel.



Model	UPMOD-3	UPMOD-8	UPMOD-10
Pixel Pitch(mm)	3,9x 7,8	7.5 x 8	10x10
LED Model	SMD1921	SMD1921	SMD1921
Brightness(nit)	6000	6000	6000
Transparency	75 %	75 %	80 %
Module size(mm)	1000 x 500	960 x 480	960 x 480 960 x 800
Operation Power	220V,AC50HZ	220V,AC50HZ	220V,AC50HZ
Module Resolution	256x64	128x60	96x48 96x80
Color Temperature	5500K-9300K	5500K-9300K	5500K-9300K
Countinous working Time (Hours)	>72	> 72	> 72
Contrast	>880:1	>880:1	>880:1
Avg. Power(W/m2)	240	280	280
Ingress Protection	IP20	IP20	IP20
Refresh rate(Hz)	>1500 HZ	1000~1500 HZ	1000~1500 HZ
Weight(kg/m2)	12kg/m2	12kg/m2	12kg/m2

