

STENCIL CLEANING MEDIA

The pH-neutral Hyperclean cleaning medium efficiently removes residues of solder pastes containing lead, lead-free and No-Clean solder pastes as well as of SMT adhesives from the underside of the stencil.

After the printing process, Hyperclean SUC 61/63 optimally wets both the cleaning roll and the underside of the stencil, so that constant high and qualitatively reproducible cleaning results are achieved.

The innovative homogeneous formula and the optimal drying behaviour minimise the smearing phenomena often observed with water-based cleaners common in the market as well as the smearing of solder paste components.

Hyperclean SUC61/63 is the perfect partner to Hyperclean PX3800 stencil wiper roll.



- ◆ Zero residue formula
- ◆ Optimized evaporation
- ◆ Low odour
- ◆ Superior cleaning
- ◆ Non deteriorating to plastics
- ◆ High flashpoint
- ◆ Developed and manufactured in EU
- ◆ SUC61A for standard applications
- ◆ SUC63S for hard-to-clean applications



	SUC61A	SUC63S
Appearance	Colourless to slightly yellow, clear	Colourless to slightly yellow, clear
Application	Ready-to-use	Ready-to-use
pH-value	Neutral	Neutral
Density at 20 °C	0,965 +/- 0,005 g/cm ³	0,821 +/- 0,005 g/cm ³
Boiling point/boiling range	>100 °C	170 °C-210 °C
System	Water based	Solvent based
Operations temperature	Room temperature	Room temperature
Transportation	Non dangerous goods	Non dangerous goods
Reliable cleaning results with	Leaded, lead-free, no-clean solder pastes, SMT-adhesives	
Packaging	1 litre, 5 litre or 20 litre	
Manufacturing	Manufactured in EU	

Storage

Store under normal conditions of 10° to 30°C and 20 to 70% R.H. in the initial packaging, away from sunlight. Shelf life is 36 months from manufacturing date.

Legal disclaimer

SMT Express believes that the information in this technical data sheet is an accurate description of the typical uses and data of the product. SMT Express, however, disclaims any liability for incidental or consequential damages, which may result from the use of the product that are beyond its control. Therefore, it is the user's responsibility to thoroughly test the product in their particular application to determine its performance, usefulness and safety. Nothing contained herein is to be considered as permission or a recommendation to infringe any patent or any other intellectual property right.