

EUROLAN Duct

Indoor 5/3,5 mm



Ordering information

Part number	E-number	Description
39P-I1-01-23WT	5044230	EuroLAN Single tube 5/3,5 mm FRLSOH Indoor
39P-I1-02-23WT		EuroLAN 2xtube 5/3,5 mm FRLSOH Indoor
39P-I1-03-23WT		EuroLAN 3xtube 5/3,5 mm FRLSOH Indoor
39P-I1-04-23WT	5044231	EuroLAN 4xtube 5/3,5 mm FRLSOH Indoor
39P-I1-07-23WT	5044232	EuroLAN 7xtube 5/3,5 mm FRLSOH Indoor
39P-I1-12-23WT	5044233	EuroLAN 12xtube 5/3,5 mm FRLSOH Indoor
39P-I1-19-23WT	5044234	EuroLAN 19xtube 5/3,5 mm FRLSOH Indoor
39P-I1-24-23WT	5044235	EuroLAN 24xtube 5/3,5 mm FRLSOH Indoor

Technical information

Characteristics	Unit	Nominal Value	Tolerances or Requirements	Standard
Flame Test	sec.		60	IEC 60332-1
Tube Test	sec.	30	Extinction ≤ 30	IEC 61386-1
Cable Test	m	1.11	Max 2.5	IEC 60332-3-24
Smoke density	%	97	≥ 60	IEC 61034-1/2
Acidity of gas	Ph	6.06	≥ 4.3	IEC 60754-2
	% Hcl	0	≤ 0.5	IEC 60754-1
	$\mu\text{S/cm}$	4.8	≤ 100	IEC 60754-2

✓ Indoor micro duct for blown fiber.

✓ Dimension 5/3,5

✓ Fire rated in acc with IEC 60332-1