

# EUROLAN Microcable

## Singlemode 3,9mm G652.d



### Ordering information

Part number	E-number	Description
39M-S1-02-39BL	4963567	Microcable 3,9 mm for air blowing 2x652.d
39M-S1-04-39BL	4963577	Microcable 3,9 mm for air blowing 4x652.d
39M-S1-08-39BL	4963587	Microcable 3,9 mm for air blowing 8x652.d
39M-S1-12-39BL	4963597	Microcable 3,9 mm for air blowing 12x652.d
39M-S1-24-39BL	4963827	Microcable 3,9 mm for air blowing 24x652.d

### Specifications

Fiber count	2-24
Strenght members	Reinforced fiberglass yarn WB (waterblocking)
Outer jacket	High density polyethylene (HDPE)
Colour	Black
Weight kg/km	12
Outer Ø (mm)	3,9 ±0,1
Tensile Load Perm/ inst (N)	150 / 200
Crush Perm / inst (N)	700 / 1200
Suggested innerduct Ø	3,0 mm
Temperature Operation	40°C to +70°C
Temperature Installation	0°C to +40°C
Min bending radius (mm)	20 x Outer Ø

- ✓ **Application:**  
For blowing in micro-ducts from 8,0 mm in inner dimensions
- ✓ **Glass:** G652.d
- ✓ **Standards:** EN 187000  
IEC 60794
- ✓ **Core:** Up to 24 fibres,  
Loose Tube embedded in gel
- ✓ **Outer sheat:** HDPE

#### Fiber colour code:

Red - Green - Blue - Yellow - Grey - Violet - Brown - Orange - White - Pink - Black - Neutral