


## PRODUKT INFORMATION MARKISVÄV

<b>Bredd:</b>	120 cm
<b>Rivstyrka varp:</b>	1570,7 N (UNI EN ISO 13934-1)
<b>Rivstyrka väft:</b>	864 N (UNI EN ISO 13934-1)
<b>Garn nr:</b>	NE 20/2
<b>Impregnering:</b>	TEFLON (UNI EN 24920)
<b>Konstruktion, varp/väft:</b>	31 - 14 /cm <sup>2</sup>
<b>Komposition:</b>	100% spinnfärgad acryl
<b>Ljushärdighet:</b>	7 - 8 (UNI EN ISO 105-B03)
<b>Vattentäthet:</b>	>300 mm (UNI EN 20811)
<b>Vikt väv:</b>	300 gr/m <sup>2</sup>

		<b>SCHEDA ARTICOLO</b>				N° PSQ 008/06 Edizione 01 Rev.00 Data 1°em.25/05/2002	
Data : 10/07/2002		Articolo: <b>TEMPOTEST STAR TREND STYLE</b>				Scheda nr. <b>046</b>	
CARATTERISTICA VALUTATA CHARACTERISTICS HAUPTMERKMALE CARACTERISTIQUES	UNITA' DI MISURA UNIT MASSEINHEIT UNITÉ	RISULTATI OTTENUTI SUI CAMPIONI RESULTS ERGEBNISSE RESULTATS				RIF. NORME	
Altezza pezza / Width Stückbreite/ Largeur	Cm	120					
Peso tessuto / Weight Gewicht/ Poids	gr/m <sup>2</sup>	300 (+ - 5%)					
Ordito/Warp /Kette/Chaîne	Fili/cm. – Ends/inch – Fäden/cm - Fils/cm.	31					
	Titolo / Count / Garnnummer / Titre	Ne 20/2					
Trama/Weft / Schuß/Trame	Trame/cm. – Picks/inch – Fäden/cm - Fils/cm.	14					
	Titolo / Count / Garnnummer / Titre	Ne 20/2					
Composizione / Composition Zusammensetzung / Composition	%	100% Fibra Acrilica outdoor tinta in massa					
Carico alla rottura / Breaking load Reißfestigkeit / Charge de rupture	N	Ordito/Warp /Kette/Chaîne	1570,7	Trama/Weft Schuß/Trame	864	UNI EN ISO 13934 – 1	
	Allungamento %	Ordito/Warp /Kette/Chaîne	28,6%	Trama/Weft Schuß/Trame	28,9%		
Impermeabilità / Impermeability / Wasserdichte / Imperméabilité		Idrorepellente / water-repellent / wasserabstossend / hydrofuge				UNI EN 24920	
Colonna d'acqua / Water column / Wassersäule / Colonne d'eau	Mm	>300				UNI EN 20811	
Solidità dei colori alle intemperie con esposizione all'aperto :  Fading resistance to the sun and the weather conditions :  Lichtechtheit der Farben im Freien :  Tenue des couleurs aux intempéries:		grado 7/8 – 8 colori tinti in massa Vedi garanzia 5 anni  7/8 – 8 degree solution dyed colours See 5 year guarantee  7/8 – 8 bei spinddüsengefärbten Farben Siehe 5 Jahre Garantie  degré 7/8 – 8 coloris teints dans la masse Voir garantie de 5 ans				UNI EN ISO 105 – B 03	
Finissaggio: Finishing: Ausrüstung: Finissage:	Antimacchia, imputrescibile, idro-oleorepellente con trattamento Teflon. Soil-resistant, mould resistant, oil and water-repellent with Teflon finishing Fleck-, wasser- und ölabbstossend, fäulnisverhütend mit Teflon Anti-tache, imputrescible, repoussant à l'huile avec finissage Teflon						
