



# DIAGONAL FRONT- MOUNTED PLOUGHS AM D 2600 S AM D 3000 S

**Effective, fast,  
and safe snow  
clearance**



Highly effective AM D 2600 S and 3000 S diagonal front-mounted ploughs are designed for versatile ploughing needs. You can easily adjust their ploughing angle, which enables you to clear snow efficiently from streets and public areas at various widths.

Easy ploughing width adjustment reduces ploughing time and costs substantially. Thanks to the effective blade angle and the ingenious wing shape, the plough has a lot lighter contact on the road. This highly decreases fuel consumption and blade wear and tear.



**ROAD INTELLIGENCE**

## Safe choice for demanding ploughing

AM D 2600 S and 3000 S diagonal front-mounted ploughs are ideal for ploughing to the right side at high speeds. However, the shape of the wing also enables you to clear snow to the left side. The plough directs the snow away from the windshield, which makes ploughing a lot easier.

The swivelling and well ejecting plough is perfect for variable working conditions. The plough can follow the road's longitudinal and transverse inclinations, which guarantees high quality and clean outcome. The ploughs are packed with safety-enhancing technical solutions that increase their lifetime.



Pictures may contain accessories.

| Technical information                             | AM D 2600 S                   | AM D 3000 S                   |
|---|-------------------------------|-------------------------------|
| Ploughing width                                   | 2,600–3,355 mm                | 3,000–3,965 mm                |
| Wing tip height                                   | 400 mm                        | 460 mm                        |
| Maximum wing height                               | 1,450 mm                      | 1,610 mm                      |
| Blade angle                                       | 43°                           | 43°                           |
| Ploughing angle, swivelling                       | 40°–0 –40°                    | 40°–0–40°                     |
| Weight (without wheels and other extra equipment) | 750 kg                        | 800 kg                        |
| Runners   | 2                             | 2                             |
| Swivelling cylinder                               | 2                             | 2                             |
| Lifting cylinder                                  | 1 (not in the loader version) | 1 (not in the loader version) |

### Head Office:

Arctic Machine Oy, Karsikonmäentie 1, FI-77800 Iisvesi, Finland  
Tel. +358 (0)20 7791 500, fax +358 (0)20 7791 501  
am@arcticmachine.com, www.arcticmachine.com

Copyright © Arctic Machine Oy. All rights reserved.

