



Komplett fordonspaket IMT-8 med dockningsstation, DC/DC konverter 11V-36V input samt RAMMount fäste.
Packetpris: 8.775 kr exkl.moms.

I-Mobile IMT-8 Android

Tillbehör som medföljer i packetpris



Teknisk Specification

CPU:	MT8382 Quad core 1,3GHz
Memory:	LPDRII 1G
Storage:	eMPC 8G
Graficcard:	
Operating System:	Android 4.4
Display:	TFT LCD 8 inch, touch type capacitive type
Backlight:	Type LED, display resolution 1024 x 768 (XGA)
Luminance:	700 nits Sunlight readable
Build in Function:	WLAN IEEE 802.11 b/g/n, integrated Blue Tooth 4.0 GPS/AGPS: 1575,42MHz
Control Switch	1 x Power on/off button, 1 x Barcode Scanner trigger button and
Buttons:	2 x User Define
Indicator:	3 (power, charging, system operation status)
Speaker & Micro:	Built-in speaker & microphone
Light sensor, E-Campass, Gyro, Gravity, Altimeter suport	
USB:	1 x USB 2.0 Type A 1 x OTG
DCJack:	1 x DC Power input
RS-232	1 x RS232 connector
Micro SD:	1 x Micro Secure Digital (SD) card slot
Expansion Docking	1 x 16 pin docking connector
PORT:	(interfase including Power, USB, Audio)
RJ45:	1 x 10/100 Ethernet
SIM Socket:	1 x SIM socket



Power

AC/DC Adapter: Input AC: 100-240V Output DC: 16V/4A
 Battery Pack: Internal battery, one cell DC 3,7V/920mAh
 External 3S1P, 3 Cell, DC 11,1V/3100mAh Option:
 External 3S2P, 6 Cell DC 11,1V/6200mAh

Physical

Dimensions: 251 x 181 x 39 mm
 Weight: 1,2 Kg with battery

Option Functions

3G: WCDMA 850/900/1900/2100MHz
 GSM/GPRS 850/900/1900/2100MHz
 GPS: High performance positioning engine. Support 50 channels GPS L1 Frequency, C/A code. SBAS: WAAS/EGNOS/MSAS
 Camera: Front (2M) & rear (5) dual camera
 Bar code scanner: 1D or 2D (UART Interface)
 MSR (USB Interface) Media formats: ISO 7811, AAMVA, and other F2F formats
 Swipe speed: 7 to 150cm per second, bi-directional
 Operating Life: 1,000,000 cycles minimum
 Smart card reader: Operates ISO 7816 microprocessor or memory card Transfer rates 9600 to 115200 bps
 Operating Life: 1.000,000 cycles minimum
 RFID: 13,56MHz Mifare DESFire Reader / ISO 15693 Reader
 Reading distance 30mm-50mm depending on tag types

Accessories

Optional: Docking station 4 x USB, 1 x RS-232, RJ45, 1 x DC in, Earphone, Microphone, Battery charging bay
 Vehicle & Wall mount, standard VESA & DC in 12-36V vehicle adapter
 Stylus
 2 Bay Battery Charger

Operating Temperature: -10°C (14°F) to +50°C (122°F),
 Storage Temperature: -20°C (-4°F) to 70°C (158°F),
 Dust Protection: IP6x (dust)IEC60529 13,4 test Edition2.1,
 Water Protection: IPx5 (water)IEC60529 13,4 test Edition2.1,
 Vibration: 5Hz to 500Hz 2g/5g ms 20Hz to 2000Hz 7,69g ms Non-operating
 Mil-STD-810G-514,6E-2 Sine
 Mil-STD-810G-514,6E-1 Random
 Drop Test: Drop Height: 1200mm, Drop Onto: 4 corner 4 Edges, 2 Faces.



Operating
 Non-operating
 Non-operating
 Non-operating